



Since 1977

...Leadership Through Research

RPM Indicator with Emergency Lock Button



Global Digital RPM Indicator is designed for use in Reactors that are equipped with Variable Frequency Drives. It comes with Emergency STOP push button

FEATURES

The instrument is provided with

1. Start Push Button with a NO contact
2. STOP Push Button with NC contact.
3. Multiturn Potentiometer for Speed Setting. (10K_ or 2K_)
4. Digital Speed Indicator

SPECIFICATIONS:

DISPLAY: 12.7 mm 7 segment 4 DIGIT LED

INPUT: 0 to 10V DC or 4 – 20mA DC (Programmable)

RANGE: 0 to 9999 Programmable

RESOLUTION: 0.1, 0.01, 0.001 Programmable

PUSH BUTTONS: START: Green, Momentary with 230V 2A NO contact

STOP: Red, Momentary with 230V 2A NC contact

SPEED SETTING: 10 TURN Potentiometer, 10K or 2K (Specify with Order)

ENCLOSURE: Flameproof Gas Gr. IIA, B

DIMENSIONS: 220 x 220 x 125mm Wall Mounting

*factory configurable

Data can change without prior notice

GLOBAL ELECTRONICS AN ISO 9001:2015 COMPANY

3-5-331, NARAYANGUDA, HYDERABAD-500029. INDIA

PH: +91 402322 1391, 23226687 FAX: +91 402322 2484 email: Info@ge-india.com URL: <http://www.ge-india.com>