



Since 1977

...Leadership Through Research

Process Indicator with RS 485



Global's multi-parameter display can display any parameter and transmit it on RS 485 Modbus Protocol.

FEATURES

Type	Flame Proof
Mounting	Wall Mounted
Display	Temperature, RPM, Time, etc
Display size	0.56 inch LED (4X4)
Types of sensors	Integral RH+T sensor
Temperatures	4 Digit (0.56 inch each)
Relative humidity	4 Digit (0.56 inch each)
Real Time Clock	4 Digit (0.56 inch each)
Status indication	4 LEDs for visual alarm, buzzer for audible alarm
Range:	
Temperatures	0 to 60.0 C with decimal point
Relative humidity	0 to 100% with decimal point
Time	hour: minutes 12to 24 hours formats 00.00
Accuracy	
Temperatures	0.25% on FS
Relative humidity	0.25% for 10 to 90% RH of 3%
Communications	
Communication Protocol	MODBUS RTU RS-485 Communication
Programmable Parameter (Minute and Hour)	Baud Rate, Parity, Node Address, Stop Bit
Read / Write Parameter	Read Process Value, Decimal Point.
Write	Hi Low Set Point.
Electrical Power Supply Details	230V AC 50Hz

GLOBAL ELECTRONICS AN ISO 9001:2015 COMPANY

3-5-331, NARAYANGUDA, HYDERABAD-500029. INDIA

PH: +91 402322 1391, 23226687 FAX: +91 402322 2484 email: Info@ge-india.com URL: http://www.ge-india.com